

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007062 A1

(51) International Patent Classification⁷: **A61H 39/06**

[KR/KR]; 139-33 Giamjeon-Dong, Sasang-Gu, Busi
617-050 (KR).

(21) International Application Number:

PCT/KR2003/002197

(74) Agent: BAEG, Seung Jun; Chungjo Building 301, 33-
2ka, Daechan-dong, Jung-gu, Pusan 600-102 (KR).

(22) International Filing Date: 20 October 2003 (20.10.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
20-2003-0023807 23 July 2003 (23.07.2003) KR
10-2003-0054550 7 August 2003 (07.08.2003) KR

(71) Applicant (for all designated States except US): HANJI
CO., LTD. [KR/KR]; 139-33 Gamjeon-Dong, Sasang-Gu,
Busan 617-050 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CI,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GI,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, L,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MV,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, U,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GN,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW)
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM)
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EI,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RC)

(72) Inventor; and

(75) Inventor/Applicant (for US only): YANG, HanJo

[Continued on next page]

(54) Title: CUPPING MOXA UTENSIL AS A HERB MEDICAL AUXILIARY



(57) Abstract: The present invention relates generally to a cupping and moxibustion device for assisting traditional East-Asian medicine. In more detail, an inner wall is provided in the lower portion of a body so that the lower portion is divided into a moxibustion part located in the inner part of the lower portion and a cupping part located in the outer part of the lower portion. a moxa pot is held above the moxibustion part, thus carrying out moxibustion, and an air discharge hole is formed on the outer wall of the body, an opening and closing unit is fitted into the air discharge hole, and air is discharged from the cupping part to the outside of the device to depressurize the cupping part, thus carrying out cupping. In this case, an air suction hole is formed on a lid provided on the upper end of the body, an air pump is connected to the air suction hole, and air is supplied to allow moxa contained in the moxa pot to be smoothly combusted. Furthermore, a smoke discharge hole is formed on the side of the body and thus, smoke generated at the time of combusting the moxa is discharged to the outside of the body.

WO 2005/007062 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

JC20 Rec'd PCT/PTO 08 SEP 2005

CUPPING MOXA UTENSIL AS A HERB MEDICAL AUXILIARY

Technical Field

5 The present invention relates generally to a cupping and moxibustion device, and more particularly to a cupping and moxibustion device for assisting traditional East-Asian medicine, whose lower portion is composed of two concentric parts, so that moxibustion is carried out in the inner part of the lower portion and cupping is carried out in the outer part of the lower portion.

10

Background Art

 In general, moxa is a perennial grass belonging to the chrysanthemum family. Moxa has strong alkalinity, has been widely used for culinary and medicinal purposes by
15 folks, and contains abundant chlorophyll, vegetable fibers, mineral of good quality and various vitamins.

 In traditional East-Asian medicine, acupuncture and moxibustion has been used as methods of improve immunity and vitality by removing stagnated blood due to abnormalities in the circulation of blood and Qi and warming Qi. Since the performance of acupuncture
20 requires the assistance of specialists, moxibustion has been widely utilized by folks from old times.

 Existing general moxibustion is classified into direct moxibustion of carrying out moxibustion with moxa placed on the skin of a patient and indirect moxibustion of carrying out moxibustion with moxa placed on garlic, ginger or salt. These types of moxibustion are
25 all problematic in that they generate heat and the influences (smoke and vapor) of moxa are

dispersed over an open indoor space to cause inconvenience and it is difficult to use the moxibustion due to difficulty in controlling temperature.

The cupping for promoting the immunity and vitality of humans by eliminating stagnated blood due to abnormality in the flow of Qi and blood and warming Qi so that Qi and blood are smoothly circulated has been also utilized widely in traditional East-Asian medicine and folk therapy. The shapes and kinds of cupping pots are various, and are mostly made of material, such as an animal horn, glass, plastic, wood and ceramic. The cupping may be classified into a single pot method of attaching a single cupping pot to the skin of a patient, a multiple pot method of attaching a plurality of cupping pots to the skin of a patient, an intermittent pot method of repeating the attaching and detaching of cupping pots to and from the skin of a patient, and a moving pot method of reciprocating cupping pots on the skin of the patient while being at the state of attaching cupping pots to the skin after applying lubricating oil to the skin. The cupping may also be classified into dry cupping of causing engorgement by attaching cupping pots to the skin of a patient, wet cupping of discharging blood by attaching cupping pots after applying acupuncture, and foaming cupping of causing skin foaming by attaching cupping pots to the skin of the patient under a high pressure.

In conventional cupping, since the effect of treatment can be achieved only by maintaining 10 to 40 cupping pots on the skin of a patient for a long time, the treatment requires a long time, and cupping pots are attached on a region without stagnated blood and, thus, causes a side effect because a plurality of cupping pots are employed. Furthermore, since the performance of cupping functions only to raise stagnated blood to the hypodermis of the skin, the effect of the treatment is weak. Accordingly, the conventional cupping is problematic in that the cupping has to be performed many times.

Accordingly, the present invention has been made keeping in mind the above problems occurring in the prior art, and an object of the present invention is to provide a cupping and moxibustion device that is capable of simultaneously carrying out moxibustion in the inner part thereof and cupping in the outer part thereof. Another object of the present invention is to provide a cupping and moxibustion device that is capable of discharging smoke generated at the time of moxibustion to the outside and facilitating the control of the temperature of the moxibustion.

In order to accomplish the above object, an inner wall is provided in the lower portion of a body so that the lower portion is divided into a moxibustion part located in the inner part of the lower portion and a cupping part located in the outer part of the lower portion, a moxa pot is held above the moxibustion part, thus carrying out moxibustion, and an air discharge hole is formed on the outer wall of the body, an opening and closing unit is fitted into the air discharge hole, and air is discharged from the cupping part to the outside of the device to depressurize the cupping part, thus carrying out cupping.

In this case, an air suction hole is formed on a lid provided on the upper end of the body, an air pump is connected to the air suction hole, and air is supplied to desirably combust moxa contained in the moxa pot. Furthermore, a smoke discharge hole is formed on the side of the body and, thus, smoke generated at the time of combusting the moxa is discharged to the outside of the body.

Brief Description of the Drawings

The above and other objects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction

with the accompanying drawings, in which:

FIG. 1 is an exploded perspective view of a cupping and moxibustion device for assisting traditional East-Asian medicine;

FIG. 2 is a partial cross-section of the cupping and moxibustion device for assisting
5 traditional East-Asian medicine; and

FIG. 3 is a cross-section of an opening and closing unit.

Best Mode for Carrying Out the Invention

10 A cupping and moxibustion device for assisting traditional East-Asian medicine according to an embodiment of the present invention will be described in detail with reference to the attached drawings below.

The cupping and moxibustion device for assisting traditional East-Asian medicine according to an embodiment of the present invention is largely comprised of a moxa holder
15 10, a body 20, a lid 30 and an opening and closing unit 40.

First, the moxa pot 10 is described below. The moxa pot 10 is closed at the top thereof and is provided with a plurality of through holes. Moxa is contained inside of the moxa pot 10. To be resistant to heat because moxa catches fire when used, and prevent heat from being transmitted to the body 20, the moxa pot 10 is manufactured by coating the
20 outside of a moxa pot body made of aluminum with ceramic having a low heat-conductivity. The upper portion of the moxa pot 10 is bent outward so that it is caught on a seat 21 described later and formed on the inside surface of the body 20.

The upper portion of the moxa pot 10 may have a diameter larger than that of the lower portion of the moxa pot 10 instead of being bent outward so that it can be caught by the
25 seat 21.

Next, the body 20 is described. The body 20 may be classified into a moxa holding part, a moxibustion part 24, and a cupping part 25. The moxa holding part is opened at the upper end thereof, is threaded at the upper portion of the outside thereof, and is provided with the seat 21 projected from a part of the inside thereof, thus catching the moxa pot 10. A smoke discharge hole 22 is formed below the seat 21 to discharge the smoke of moxa. The smoke discharge hole 22 extends outward to be connected to a smoke discharge pipe 70. In this invention, one end of the smoke discharge pipe 70 is connected to the smoke discharge hole 22 and the other end of the smoke discharge pipe 70 is connected to the outside of a room so that smoke generated at the time of moxibustion is discharged to the outside of the room.

The lower portion of the body 20 may be divided into the moxibustion part 24 located in the inner part of the lower portion and the cupping part 25 located in the outer part of the lower portion. The moxibustion part 24 and the cupping part 25 are divided by an inner wall 23. The moxibustion part 24 is opened at the upper and lower ends thereof and, thus, forms a passage that transmits heat and smoke, generated when moxa held in the moxa holding part burns, to the skin of a patient. The cupping part 25 is divided from the moxa holding part and the moxibustion part 24 by the inner wall 23 and is provided with an outer wall formed by extending the outer wall of the moxa holding part downwardly. An air discharge hole 26 is formed on the outer wall of the cupping part 25 to eliminate air from the cupping part 25.

Next, the lid 30 is described below. The lid 30 is combined with the upper portion of the body 20 so that the smoke of moxa is prevented from being discharged from the body 20 to the outside of the device. The inside of the lid 20 is threaded so that the threaded portion of the lid 20 engages with the threaded portion of the body 20. In this case, a packing may be provided inside of the lid 30 to improve the sealing effect between the lid 30

and the body 20. Prominences and depressions may be formed on the outside of the lid 30 to facilitate the opening and closing of the lid 30.

An air suction hole is formed on the top of the lid 30. The air suction hole is extended upwardly to be connected to an air suction pipe 61. The upper end of the air suction pipe 61 is connected to an air pump 60 so that air can be drawn through the air suction hole. A valve 62 is mounted on the air suction pipe 61 to control the flow of air. The purpose of the valve 62 is to maintain the appropriate temperature of moxibustion by controlling the amount of air drawn into the inside of the body 20.

Next, the opening and closing unit 40 is described below. The opening and closing unit 40 is made of soft rubber or the like, and is inserted into the air discharge hole 26 of the body 20. A hole 41 is formed inside of the opening and closing unit 40 and communicates with the inside of the body 20. An incision 42 is formed through the projected portion of the opening and closing unit 40 so that the incision 42 is opened and the inside of the cupping part 25 communicates with the outside of the body 20 when the projected portion is pressurized from the outside of the device and the incision 42 is closed when the projected portion is depressurized.

Accordingly, when a compressor 50 is coupled to the opening and closing unit 40, the incision 42 is opened. When the compressor 50 is operated and, thus, air is discharged from the cupping part 25, the air pressure of the cupping part 25 is decreased. At this time, the compressor 50 is removed from the opening and closing unit 40, the incision 42 of the opening and closing unit 40 is closed and air is prevented from being drawn through the air discharge hole 26 from the outside of the device.

The operation of the moxibustion and cupping device for assisting traditional East-Asian medicine according to the embodiment of the present invention is described below.

After the lid 30 is removed from the body 20 and moxa is placed in the moxa pot 10,

the moxa is ignited. The body 20 is closed to prevent smoke from leaking to the outside of the body 20 by putting the lid 30 on the body 20 after the moxa pot 10 is seated in the body 20. At this time, when the air suction pipe 61 connected to the air pump 60 is connected to the air suction hole 31 of the lid 30, and the smoke discharge pipe 70 is connected to the smoke discharge hole 22 at one end thereof and is extended to the outside of the room at the other end thereof.

After the cupping and moxibustion device is placed on the skin of the patient, the compressor 50 is connected to the air discharge hole 26, so that air is eliminated from the cupping part 25 and vacuum is formed in the cupping part 25. Air is drawn into the body 20 by operating the air pump 60 and opening the valve 62. Accordingly, the air moves from a position above the moxa pot 10 through the inside of the moxa pot 10 to the through holes formed on the bottom of the moxa pot 10. Further, the air moves downward together with the heat and smoke generated by the combustion of the moxa and, thus, applies moxibustion to the skin located below the moxibustion part 24. Thereafter, the smoke is discharged to the outside of the room through the smoke discharge hole 22 formed on the side of the body 20. In this case, the temperature of the moxibustion is maintained at a desired value by controlling the amount of air drawn into the body 20 using the valve 62 attached to the air suction pipe 61.

When the moxibustion is completed, the cupping and moxibustion device is removed from the skin, sap is removed by wiping out the skin.

Industrial Applicability

As described above, in accordance with the cupping and moxibustion device for assisting traditional East-Asian medicine according to the present invention, stagnated blood

is circulated by means of the moxibustion part located in the inner portion of the device under the action of the smoke and heat of moxibustion and the toxin of stagnated blood is discharged to the outside of the skin by means of the cupping part located in the outer portion of the device, thus maximizing the effect of treatment.

- 5 Furthermore, smoke can be discharged to the outside of a room, and the temperature of moxibustion can be automatically adjusted by controlling the amount of air drawn using the valve attached to the air suction pipe, thus facilitating the use of the device.

Claims

1. A cupping and moxibustion device for assisting traditional East-Asian medicine, comprising:

5 a moxa pot (10) whose upper end is opened, whose bottom is provided with a plurality of through holes, and whose inside holds moxa;

a body (20) whose upper end is opened, on whose outside surface a threaded portion is formed, on whose inside surface a seat (21) is formed to hold the moxa pot (10), below whose seat (21) a smoke discharge hole (22) is formed, whose lower portion is divided into a moxibustion part (24) located in an inner part of the lower portion and a cupping part (25) located in an outer part of the lower portion, the moxibustion part (24) being opened at upper and lower ends thereof to communicate with an upper portion of the body (20), the cupping part (25) being opened at a lower end thereof and being closed at an upper end thereof to divide the upper portion of the body (20) and the moxibustion part (24) from each other and being provided with an air discharge hole (26) on an outer wall thereof;

15 a lid (30) on whose inside surface a threaded portion is formed so that the threaded portion of the lid (30) is engaged with the threaded portion formed on the upper portion of the body (20) to cover the upper end of the body (20), and whose upper end an air suction hole (31) is formed; and


20 an opening and closing unit (40) tightly fitted into the air discharge hole (26) of the body (20), projected from the body (20) and connected to a compressor (50) so as to maintain a pressure of the cupping part (25) by controlling an air flow between the cupping part (25) and an outside of the body (20).

2. The cupping and moxibustion device as set forth in claim 1, wherein the smoke


discharge hole (22) is connected to a smoke discharge pipe (70) to allow smoke generated at the time of moxibustion to be discharged to an outside of the device.

3. The cupping and moxibustion device as set forth in claim 1, wherein the air
5 suction hole (31) of the lid (30) is connected to a first end of an air suction pipe (61), a second end of the air suction pipe (61) being connected to an air pump (60) to allow air to be drawn to an inside of the body (20).


4. The cupping and moxibustion device as set forth in claim 3, wherein the air
10 suction pipe (61) is provided with a valve (62) capable of controlling a flow of the air.

1 / 3
FIG. 1

2 / 3
FIG. 2



3 / 3
FIG. 3



INTERNATIONAL SEARCH REPORT

 International application No.
 PCT/KR2003/002197
A. CLASSIFICATION OF SUBJECT MATTER**IPC7 A61H 39/06**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7 A61H 7/00, A61H 39/06, A61B 17/36

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Patents and Applications for inventions since 1975

Korean Utility models and Applications for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

NPS, PAJ, FPD, USP

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	KR 2002-0096438 A (Bae, Sam Hoon) 31 December 2002 see the whole document	1-4
Y	KR 20-0234572 Y1 (Kim, Young Hoon) 26 September 2001 see the whole document	1-4
A	US 3946733 A (Jin, Suk Han) 30 March 1976 see the whole document	1
A	JP 52-41488 A (Daiko Iryoki Co., Ltd) 31 March 1977 see the whole document	1
A	JP 10-52474 A (Ben Seigen) 24 February 1998 see the whole document	1
A	KR 20-0254568 Y1 (Yang, Han Jo) 01 December 2001 see the whole document	1

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

19 APRIL 2004 (19.04.2004)

Date of mailing of the international search report

20 APRIL 2004 (20.04.2004)

Name and mailing address of the ISA/KR


 Korean Intellectual Property Office
 920 Dunsan-dong, Seo-gu, Daejeon 302-701,
 Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

SONG Jong Min

Telephone No. 82-42-481-8131



BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2003/002197

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
KR 2002-0096438 A	31.12.2002	NONE	
KR 20-0234572 Y1	26.09.2001	NONE	
US 3946733 A	30.03.1976	NONE	
JP 52-41488 A	31.03.1977	NONE	
JP 10-52474 A	24.02.1998	KR 177531 B!	01.04.1999
KR 20-0254568 Y1	01.12.2001	NONE	